

Corporate Address


Equipson

Pol.Ind. L'Alteró, Av. Saler 14

CP: 46460 – Silla (Valencia), SPAIN



General Lighting MAS-CL08-series



MAS-CL08x-530 / MAS-CL08x-540

Feature

- Indoor - LED light source protected from dust.
- Thermally engineered heat-sink, robust and ensure LED-source cooler operation
- Precision reflector to achieve precision beam control.
- Glare control reflector creates visual comfort, cut-off angle 25°

Application

General lighting, office lighting, meeting room, high ceiling spaces

Standards

- Fixture with LM80-report
- LED-Driver comply to CE with short current protection, NO load protection, Overload Protection.

Temperature

- Ambient operating temperature: -5°C ~ +40°C
- Storage temperature: +25°C

LED-Driver (AC220-240V 50/60HZ)

- Standard-supply with non-dim driver
- choice of ELV dimmable driver, 1~10V-control-driver, Dali-Control-Driver

Specifications:

Power	30W	40W	
LED Source	COB	COB	
CRI	Ra≥80 (Ra>88 optional)	Ra≥80 (Ra>88 optional)	
CCT	2700 / 3000 / 4000 / 5000 / 6500K		
Beam Angle	R:15°30°45° / S:24°36°60°	R:15°30°45° / S:24°36°60°	
SystemLumen Flux	2250lm-2450lm	2350lm-2550lm	
LM report	LM80	LM80	
Rated Lifespan	>50000HRS(L70)	>50000HRS(L70)	
Overall Dimension	φ162mm*H115.5mm		
Cut-out hole size	ø150mm		
Material	Aluminum Die Casting		
IP Rating	IP 20 / IP 40		
Color of Ring	White (Normal)	Black	Silver